

# THE ID PACK PRODUCT RANGE



THE RIGHT  
ID PACK  
FOR YOUR  
APPLICATION



	ID PACK 32 x 48	ID PACK 40 x 48	ID PACK 45 x 48
Outside dimensions (L x W x H)	32.48" x 48.23" x 35.28" 825 x 1225 x 896 mm	40.35" x 48.23" x 43.15" 1025 x 1225 x 1096 mm	45.08" x 48.23" x 46.81" 1145 x 1225 x 1189 mm
Inside dimensions (L x W x H)	29.41" x 45.28" x 28.03" 747 x 1150 x 712 mm	37.68" x 45.00" x 35.91" 957 x 1143 x 912 mm	42.40" x 45.16" x 39.57" 1077 x 1147 x 1005 mm
Volume	21.55 ft <sup>3</sup> / 610 L	34.79 ft <sup>3</sup> / 985 L	44.50 ft <sup>3</sup> / 1260 L
Netto payload weight acc. to ASTM 4169-16*	1100 lb / 500 kg	1100 lb / 500 kg	1100 lb / 500 kg
Netto permissible top load acc. to ASTM 4169-16*	4850 lb / 2200 kg	4850 lb / 2200 kg	4850 lb / 2200 kg
Tare weight	51 lb / 23 kg	64 lb / 29 kg	73 lb / 33 kg
Volume reduction	74 %	79 %	80 %



	ID PACK 32 x 48	ID PACK 40 x 48	ID PACK 45 x 48
A**	70.04" / 1779 mm	85.75" / 2178 mm	87.28" / 2217 mm
B	35.28" / 896 mm	43.15" / 1096 mm	46.81" / 1189 mm
C	3.74" / 95 mm	3.74" / 95 mm	3.74" / 95 mm
D**	17.95" / 456 mm	17.95" / 456 mm	17.95" / 456 mm
E	9.25" / 235 mm	9.25" / 235 mm	9.25" / 235 mm

\* Tested by the VDZ competence and testing center for packaging and transport, Giselherstr. 34, 44319 Dortmund, Germany (certificate number: 8021). Permissible top load may vary due to the level of assurance (level I, level II, level III).

\*\* Subtract 0.55" (14 mm) per stack interface to account for stack nesting.